

PBSSF-S-R - 10 /1 Gigabit (SM) Fiber Bypass Switch Stand Alone Unit

Introduction


Silicom PBSSF-S-R is external Bypass switches for 10 /1 fiber Gigabit Ethernet networks. The Silicom Bypass switch protects from network failures and Network maintenance by ensuring network integrity during power loss. Silicom Bypass switch includes Network ports, Monitor ports and control port. The Network ports are used to connect to Switch / Router Network connections. The Monitor ports are used for an in-line networking device. The control port is used to control the mode of the Bypass switch. On power on, the mode of the Bypass switch is set to Normal, on power lose, the mode of the Bypass switch is set to Bypass .



Functional Description


In Normal mode, the Bypass switch diverts the data from the Network ports data to the Monitor ports.

Figure: 1 - Normal Mode Functional Block Diagram



In Bypass mode, the Network data traffic routed directly to the other Network port. And the Monitor data traffic routed directly to the other Monitor port.

Figure: 2 - Bypass Mode Functional Block Diagram



Key features:

Bypass:

- Bypass Ethernet ports on Power lose.
- Software Reliable Passive solution.
- High speed switching.
- Low insertions loss.
- Throughput not affected and no added delay.

PBSSF-S-R:

- Supports Fiber Gigabit Ethernet (1000Base-LX).
- Supports Long Range Fiber 10 Gigabit Ethernet (10GBase-LR)

Technical Specifications:

Fiber Gigabit Ethernet Technical Specifications - (1000Base-LX) Adapters:

IEEE Standard / Network topology:	Fiber Gigabit Ethernet, 1000Base-LX (1310nm)
Data Transfer Rate:	2000Mbit/s in full duplex mode per port
Cables and Operating distance:	Single-Mode fiber: 9um 2500m maximum at 9um ** ** Theoretical Distance – Defined as half a distance as stated by the IEEE 802.3

	standard
Insertion loss (Normal)	Typical: 1.2 dB Maximum: 1.6 dB
Insertion Loss (Bypass Mode)	Typical: 1.2 dB Maximum 1.6 dB

Fiber Gigabit Ethernet Technical Specifications - (10GBase-SR) Adapters:

IEEE Standard / Network topology:	Fiber Gigabit Ethernet, 10GBase-LR (1310nm)
Data Transfer Rate:	20Gbit/s in full duplex mode per port
Cables and Operating distance:	Multimode fiber: 9um 5000m maximum at 9 um ** Theoretical Distance – Defined as half a distance as stated by the IEEE 802.3 standard
Insertion Loss (Normal Mode)	Typical: 1.2 dB Maximum: 1.6 dB
Insertion Loss (Bypass Mode)	Typical: 1.2 dB Maximum: 1.6 dB

General Technical Specification:

PBSSF-S : General Technical Specifications

Size:	x 152mm x 120.5mm x 24mm (6" x 4.75" x 1")
Voltage:	+5V
Weight:	690 gram (24.4 oz)
Power Consumption:	(0.184W) 40mA at 4.6V
Operating Humidity:	0%–90%, non-condensing
Operating Temperature:	0°C – 50°C (32°F - 122°F)
Storage Temperature:	-20°C–65°C (-4°F–149°F)
EMC Certifications:	ClassB
MTBF*:	> 50 years

PBSSF-S : LED Connector Specifications

LEDs:	(1) LED Blue LED indicating Power /Bypass
Connectors:	(2) Quad LC per segment RJ45 Control connector – Pin 5 5v, Pin 4 GND, pin 1 and pin 2 are shorted

Order Information:

P/N	Description	
PBSSF-S-R	10 /1 Gigabit (SM) Fiber Bypass Switch Stand Alone Unit	

Note: Model P/N /-R
-R: RoHS Compliant / Lead free adapter.

1V0